




EW66

Standby power : 66 KVA/52KW

Prime power : 60 KVA/48KW

Standard features

- Engine : CUMMINS , 4BTA3.9-G2
- Charge alternator : 24V
- Governor : Electrical
- Generator : STAMFORD , UCDI224E
- Single bearing alternator IP 23
- Insulation class H/H
- Radiator 50°C max with coolant cap
- Skid and vibration isolators
- Dry type air filter
- Main line circuit breaker
- 24V battery and cable
- Industrial muffler
- User's manual



Weight and Dimensions

GEN-Set	Dimension (Largo×Ancho×Alto)	Peso
Open Type	1820mm×820mm×1350mm	916 Kg
Silent Type	2396mm×1056mm×1723mm	1305 Kg

Generator Ratings

Voltage	Hz	Phase	Power factor	Standby AMP	Standby Rating (KVA/KW)	Prime Rating (KVA/KW)
400/230	50	3	0.8	94	66/52	60/48

Engine Data

Manufacturer/Model	CUMMINS 4BTA3.9-G2 4-cycle
Cylinder /Arrangement	4 / L
Displacement	3.9 L
Bore and Stroke	102 mm×120 mm
Compression ratio	16.5 : 1
Rated RPM	1500 RPM
Max. stand by power at rated RPM	55KW
Frequency regulation , steady state	≤ 1%
Governor : type	Electrical

Exhaust System

Exhaust gas flow	166 L/S
Exhaust temperature	475°C
Max back pressure	76mmHg



Fuel System

Fuel consumption 100% (of the Prime Power)	11 L / h
--	----------

Oil system

Total oil capacity w/filters	10.9 L
------------------------------	--------

Air intake

Engine air flow	248 m3/h
-----------------	----------

Coolant System

Radiator & engine capacity	17,9 L
Max water temperature	105°C
Thermostat	82-94°C

Generator Data

Manufacturer / Type	STAMFORD UCI224E
Number of phase power	3
Factor (Cos Phi)	0.8
Pole : number	4
Bearing : number	1
Coupling	Direct
Exciter type	Brushless SHUNT
Insulation : class , temperature rise	H / H
protection	IP23

Control panel



Specifications :

Frequency meter , Ammeter , Voltmeter , Alarms and faults
Oil pressure , water temperature , No start-up , Overspeed ,
Min/max battery voltage , Low fuel level , Emergency stop

Engine parameters:

Hours counter , Oil pressure , water temperature